

2264.4wh Portable Outdoor Power Station 21700 Ternary Lithium **Batteries**

Basic Information

- Brand Name:
- TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD







Product Specification

- Rated Capacity:
- Weight (net Weight):
- Weight (including
- Accessories):
- Product Size:

• Highlight:

- Recharging Input Voltage: 12-26V
- Recharging Input Power:
- AC/DC Adapter:
- Solar Charging Input: 12V-26V (maximum 155W)
 - Portable Outdoor Power Station 21700 Ternary, 2264.4wh Portable Outdoor Power Station

AC 100-240V, DC 12-26V 6.25A

460mmx366mmx260mm

2264.4wh

155W Max

≈34kg

≈35kg

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Product name: 2000W ternary lithium battery for self driving, camping, portable emergency energy storage, outdoor mobile power supply

Product Description

Quick Details

- 1. LCD display
- 2. DC output
- 3. Cigarette lighter socket output
- 4. USB output
- 5. PV input
- 6. DC input
- 7. Anti collision strip
- 8. Wireless charger
- 9. SOS mode and LED lights
- 10. Air inlet with cooling fan
- 11. AC output
- 12.1000W
- 13. Ternary lithium battery

Describe

HDMP2000 has an independent battery compartment and is a portable energy storage power supply product that meets the American AC power standards with a rated AC output power of 2000W. It uses 21700 ternary lithium batteries and a battery capacity of 2264.4Wh. It is suitable for household emergency power consumption, outdoor travel, emergency disaster relief, outdoor work, and other occasions.

This product has a total AC rated output power of 2000W, with two 110V AC outputs, three USB-A outputs that meet the QC3.0 standard, one USB-C output that meets the PD60 standard, two DC5525 outputs, and one cigarette lighter port output. It has a built-in 5W LED lighting and SOS alarm function.

This product supports 110V AC charging through the standard 24V/6.25A AC adapter, as well as DC photovoltaic 18V/100-200W charging and DC 12V car charger to charge the product.

| General specifications | | | | |
|----------------------------------|------------------------------|-----------|--|--|
| General specifications | | | | |
| rated capacity | 2264.4wh | | | |
| Weight (net weight) | ≈34kg | | | |
| Weight (including accessories) | ≈35kg | | | |
| Product size | 460mmx366mmx260mm | | | |
| input | | | | |
| Recharging input voltage | 12-26V | | | |
| Recharging input power | 155W Max | | | |
| AC/DC adapter | AC 100-240V, DC 12-26V 6.25A | | | |
| Solar charging input | 12V-26V (maximum 155W) | | | |
| Car charger | 12V==10A maximum | | | |
| output | | | | |
| AC output voltage | 110V±10%/60Hz | | | |
| Rated output power | 2000W | | | |
| Output waveform | Pure sine wave | | | |
| Overload protection power supply | 2100±80W | | | |
| Cigarette lighter socket output | 12V===10A | Total 8A | | |
| DC55 * 2.5 output x2 | 12V===10A | I Ulai OA | | |
| USB output | QC3.0/18W | | | |
| C-type output | PD60W | | | |
| battery | | | | |
| Standard battery capacity | 44.4V 51Ah | | | |

| working temperature | 14-104 (-10-40) |
|----------------------|------------------|
| Charging temperature | 32-104 (0-40) |
| Storage temperature | -4-113 (-20-45) |

Matters needing attention

1. Do not put the product into water!

2. Do not heat the product or approach a fire source! Do not disassemble or modify the product without authorization! Do not forcefully strike the product! Otherwise, it may cause the battery to overheat, short circuit, catch fire or malfunction, shorten its lifespan, and other hazards.

3. Do not use or place this product under high temperatures (scorching sunlight or in very hot cars), as this may cause the battery to overheat, catch fire, malfunction, shorten lifespan, and other hazards.

4. Do not disassemble or disassemble the power supply

5. Do not short-circuit the power battery

6. It is prohibited to use non dedicated chargers to charge the power supply, as it may cause danger;

7.Do not directly touch the leaking battery. Leaking electrolyte can cause skin discomfort. In case the electrolyte enters the eyes, rinse with clean water as soon as possible, do not rub the eyes, and promptly seek medical attention;

Application

Suitable for household emergency electricity use, outdoor travel, emergency relief, outdoor work, and other occasions.

Frequently Asked Questions

- 1.Can I place a sample order for an outdoor mobile power supply?
- 2. What is the delivery time?
- Is there a minimum order quantity limit for outdoor mobile power orders?
- 4. How to transport the goods and how long will it take for delivery?
- 5. How to process outdoor mobile power orders?(Requirements, quotations, samples, deposits, production)
- 6. Is it possible to label?
- 7. How long is the warranty period?
- 8. How to handle faults?

| TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD | | | |
|---|-------------|-----------------------|----------------------------|
| Q | 13752486626 | huangwei@toec-iot.com | e outdoorpower-station.com |
| No. 6, Mount Taishan Road, Hexi District, Tianjin | | | |