

Wireless Charger Outdoor Battery Power Supply Solar Compatible

Our Product Introduction

Basic Information

- Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD
- Model Number: HDMP2000



Product Specification

- Input: AC 100-240V, 50/60Hz
- Product Name: Portable Outdoor Power Station
- Protection: Short Circuit/Overcharge/Over Discharge/Overload/Over Temperature Protection
- Rechargeable: Yes
- Solar Compatible: Yes
- Warranty: 12 Months
- Highlight: **Wireless Charger Outdoor Battery Power Supply**
, Outdoor Battery Power Supply Solar,
Wireless Charger solar portable power supply

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Portable Outdoor Power Station HDMP2000, 2000W, LCD Display, DC/AC Output, Wireless Charger
Product Description

1. LCD display
2. DC output
3. Cigarette lighter socket output
4. USB output
5. PV input
6. DC input
7. Anti collision strip
8. Wireless charger
9. SOS mode and LED lights
10. Air inlet with cooling fan
11. AC output
12. 1000W
13. Ternary lithium battery

Describe

HDMP2000 has an independent battery compartment and is a portable energy storage power supply product that meets the American AC power standards with a rated AC output power of 2000W. It uses 21700 ternary lithium batteries and a battery capacity of 2264.4Wh. It is suitable for household emergency power consumption, outdoor travel, emergency disaster relief, outdoor work, and other occasions.

This product has a total AC rated output power of 2000W, with two 110V AC outputs, three USB-A outputs that meet the QC3.0 standard, one USB-C output that meets the PD60 standard, two DC5525 outputs, and one cigarette lighter port output. It has a built-in 5W LED lighting and SOS alarm function.

This product supports 110V AC charging through the standard 24V/6.25A AC adapter, as well as DC photovoltaic 18V/100-200W charging and DC 12V car charger to charge the product.

General specifications

General specifications		
rated capacity	2264.4wh	
Weight (net weight)	≈34kg	
Weight (including accessories)	≈35kg	
Product size	460mmx366mmx260mm	
input		
Recharging input voltage	12-26V	
Recharging input power	155W Max	
AC/DC adapter	AC 100-240V, DC 12-26V 6.25A	
Solar charging input	12V-26V (maximum 155W)	
Car charger	12V==10A maximum	
output		
AC output voltage	110V±10%/60Hz	
Rated output power	2000W	
Output waveform	Pure sine wave	
Overload protection power supply	2100±80W	
Cigarette lighter socket output	12V===10A	Total 8A
DC55 * 2.5 output x2	12V===10A	
USB output	QC3.0/18W	
C-type output	PD60W	
battery		
Standard battery capacity	44.4V 51Ah	
working temperature	14-104 (-10-40)	
Charging temperature	32-104 (0-40)	
Storage temperature	-4-113 (-20-45)	

Application

Suitable for emergency household electricity use, outdoor travel, emergency relief, outdoor work, and other occasions. Intelligent LCD touch screen, visual human-machine interaction interface, information display, setting operation, etc.



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin