

PV Input Portable Outdoor Power Station Rechargeable USB Outputs

Our Product Introduction

for more products please visit us on outdoorpower-station.com

Basic Information

- Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD
- Model Number: HDG1000Pro



Product Specification

- Product Name: Portable Outdoor Power Station
- Rechargeable: Yes
- Safety Protection: Yes
- Solar Compatible: Yes
- Warranty: 1 Year
- Weight: 9.8lbs
- Highlight: PV input Portable Outdoor Power Station, Portable Outdoor Power Station Rechargeable, rechargeable power station USB Outputs

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Portable 1000W Outdoor Power Station with LCD Display & DC/Cigarette Lighter/USB Outputs

Product Description

1. LCD display
2. DC output
3. Cigarette lighter socket output
4. USB output
5. PV input
6. DC input
7. Anti collision strip
8. Wireless charger
9. SOS mode and LED lights
10. Air inlet with cooling fan
11. AC output
12. 1000W
13. Ternary lithium battery
14. Parallel operation

Describe

HDG1000Pro is a portable energy storage power supply product that complies with American AC power standards, with a rated AC output power of 1000W, and uses a 21700 ternary lithium battery with a battery capacity of 999Wh. It is suitable for home emergency power consumption, outdoor travel, emergency relief, and outdoor work.

This product has a total AC rated output power of 1000W, with two 110V AC outputs, three USB-A outputs that meet the QC3.0 standard, one USB-C output that meets the PD60 standard, two DC5525 outputs, and one cigarette lighter port output. It has a built-in 5W LED lighting and SOS alarm function, and supports 10W wireless charging function.

This product supports 110V AC charging through the standard 24V/6.25A AC adapter, as well as DC photovoltaic 18V/100-200W charging and DC 12V car charger to charge the product.

General specifications

General specifications		
Rated capacity	999wh	
Weight (net weight)	≈8.8kg	
Weight (including accessories)	≈9.8kg	
Product size	312mmx190mmx190mm	
input		
Recharging input voltage	12-26V	
Recharging input power	155W Max	
AC/DC adapter	AC 100-240V, DC 12-26V 6.25A	
Solar charging input	12V-26V (maximum 155W)	
Car charger	12V===8A maximum value	
output		
AC output voltage	110V±10%/60Hz	
Rated output power	1000W	
Output waveform	Pure sine wave	
Overload protection power supply	1100±80W	
Cigarette lighter socket output	14V===8A	Total 8A
DC55 * 2.5 output x2	14V===8A	
wireless charger	10W	
USB output	QC3.0/18W	
C-type output	PD60W	
battery		
Standard battery capacity	3.7V 270Ah	
working temperature	14-104 (-10-40)	
Charging temperature	32-104 (0-40)	
Storage temperature	-4-113 (-20-45)	

Application

Suitable for emergency household electricity use, outdoor travel, emergency relief, outdoor work, and other occasions.
Emergency charging of automobiles
At any time
Preparing for self driving travel



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin