



Basic Information

Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY

CO., LTD

• Model Number: The HD-AMB106



Product Specification

Plug Model: NEMA 5-15P
Product Type: Plug And Charge
Equipment Weight: About 3.4KG

• Cable Length: 5 Meters [supports Customized Line Length]

Maximum Power: 7.4KWOutput Voltage: AC240V

• Highlight: NEMA 5-15P Plug ev wall charger,

5m Cable ev wall charger, 40A Max Current ev wall charger

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Home EV Charging Station with NEMA 5-15P Plug, 5m Cable & 40A Max Current Product Description

- 1. Portable household portable charger
- 2. After charging and use, it can be carried with the vehicle
- 3. The power of the device is as low as 3W in the on-machine state, saving energy and low consumption
- 4. Three color charging indicator light, indicating charging related values

Describe

The HD-AMB106 charging gun is a portable charging product that meets the American AC power standards, with a rated maximum AC output power of 7.4KW and a weight of approximately 3.4KG. It is suitable for household new energy on-board chargers, outdoor travel, emergency relief, and outdoor work.

General specifications

General specifications		
Detailed parameters		Parameter Details
Name and model		HD-AMB106
Appearance structure	plug model	NEMA 5-15P
	product type	Plug and Charge
	Shell material	Gun Head - Control Box PC9330
	Equipment size	Gun head 230 * 98 * 58mm/control box 220 * 98 * 48mm [H * W * D]
	Installation method	Floor/wall mounted
	Install components	Wall mounted screw accessories
	Wiring method	Up in and down out
	Equipment weight	About 3.4KG
	Cable specifications	3*6mm²+0.75mm²
	Cable length	5 meters [supports customized line length]
Electrical indicators	input voltage	AC240V
		50Hz/60Hz
	maximum power	7.4KW
	output voltage	AC240V
	Output current	32A
	standby power	3W
Environmental indicators	usage scenarios	Indoor/Outdoor
	Working humidity	5% -95% non condensing
	working temperature	-30 +50
	Working altitude	<2000 meters
	Protection level	Gun head IP67/control box IP67
	Cooling method	Natural cooling
	Safety regulations and standards	
	Flame retardant grade	UL94 V0
	Product Certification	UL,FCC
Functional design	man-machine interface	LED indicator light
	communication interface	/
Packaging specifications	Box gauge/weight	505*505*298mm
safety design	Undervoltage protection, overvoltage protection, overload protection, overcurrent protection, over temperature protection, leakage protection, grounding protection, lightning protection, electrostatic protection, flame retardant protectionretardant protection	

Application

Suitable for American standard new energy vehicle home emergency electricity, outdoor travel, emergency relief, outdoor work and other occasions, charging anytime and anywhere.

Product features: plugs, indicator lights, cables.







13752486626





