



High magnification polymer lithium-ion automotive emergency starting power supply

Our Product Introduction

for more products please visit us on outdoorpower-station.com

Basic Information

- Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD
- Model Number: HD3



Product Specification

- Built-in Battery: High Rate Polymer Lithium Battery
- Battery Capacity: 20000mAh-74WH
- Product Features: Display &PD&QC3.0&DC Output
- LED Lights: Constant, Strobe, SOS
- Power Features: TYPE-C Charging Input /PD
Output:5V3A,/9V3A/12V3A/15V3A/20V5A
5V3A/9V3A/12V3A/15V3A,/20V5A USB1:
QC3.0/5V3A/9V2A/12V1.5A
- Operating Temperature: -30 -65
- Shell Flame Retardant Grade: V0
- Lifecycle: >1000 Times
- Product Net Weight: About 600g

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

High magnification polymer lithium-ion automotive emergency starting power supply:

HD3 is a portable, outdoor emergency, and long-lasting automotive emergency power supply that meets American AC power standards. It uses a high magnification polymer lithium-ion battery and is suitable for home emergency power, outdoor travel, emergency relief, and outdoor work.

The battery capacity of this product is 20000mAh, using an IC intelligent protection chip that intelligently matches the voltage and current of the car. The nine fold protection is effective (polymer lithium battery, constant current protection, voltage stabilization protection, overshoot protection, anti backflow protection, temperature protection, short circuit protection, overcurrent protection, and over discharge protection) to ensure battery stability. It is suitable for 12V diesel gasoline vehicles, regardless of vehicle type, fearless displacement, bidirectional fast charging, high-power output, and durable.

General specifications

General specifications	
Built-in battery	High rate polymer lithium battery
Battery capacity	20000mAh-74WH
Product Features	Display &PD&QC3.0&DC output
Power Features	TYPE-C charging input /PD output: 5V3A,/9V3A/12V3A/15V3A/20V5A 5V3A/9V3A/12V3A/15V3A,/20V5A USB1: QC3.0/5V3A/9V2A/12V1.5A USB2:5V/2A DC output: 12V-16.8V8A
Starting current	500A/600A
Peak current	1000A/1200A
LED Lights	Constant, Strobe, SOS
lifecycle	>1000 times
Fully charged time	3-4H
Shell material	PC
Shell Flame retardant grade	V0
Operating temperature	-30 -65
Product dimension	192*88*44mm(LWH)
Product net weight	about 600g
Product color matching	Can be freely matched by customers (quantity required)
Product packaging	toolbox
Tool box dimension	20.5*22.5*5.5cm (LWH)
Accessories(Default)	Intelligent jump cables

note

- 1,Please do not use this power supply for usage scenarios outside of its design scope.
- 2,During use, please avoid letting children or pets come into contact with the power supply and connecting wires to prevent electric shock hazards.
- 3,Do not use emergency powe humid environments to prevent leakage accidents.
- 4,Do not overcharge or discharge.
- 5,Do not directly touch the leaking battery. Leaking electrolyte can cause skin discomfort. In case the electrolyte enters the eyes, rinse with clean water as soon as possible.

Application

Suitable for household emergency electricity use, outdoor travel, emergency relief, outdoor work, and other occasions.

frequently asked question

- 1,What is the delivery time?
- 2,What is logistics? Express delivery?
- 3,Is there a minimum order quantity limit?
- 4,Is there a minimum order quantity limit?
- 5,How to handle orders for automotive emergency power supplies? (Requirements, quotations, samples, deposits, production)



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin