

AC230V Home Fast Charger For Electric Car With 3.5KW Rated Power

Basic Information

- Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD
- Model Number: HD-OB104



Product Specification

- Plug Model: 32A Industrial Plug
- Installation Method: Floor/wall Mounted
- Install Components: Wall Mounted Screw Accessories
- Wiring Method: Up In And Down Out
- Equipment Weight: About 3.4KG
- Cable Specifications: 3.6mm² +0.75mm²
- Highlight: **AC230V Home Fast Charger For Electric Car ,
Home Fast Charger For Electric Car 3.5KW**

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Portable Home EV Charging Station with 3.5KW Rated Power

Product Description

1. Portable household portable charger
2. After charging and use, it can be carried with the vehicle
3. When the device is in standby mode, the power is as low as 3W, saving energy and low consumption
4. Three color charging indicator light, indicating charging related values

Describe

The HD-OB104 charging gun is a portable charging product that complies with the European Union's AC power consumption standards, with a rated maximum AC output power of 3.5KW and a weight of approximately 2KG. It is suitable for household new energy on-board chargers, outdoor travel, emergency relief, outdoor work, and other occasions.

General specifications

Detailed parameters		Parameter Details
Name and model		HD-OB104
Appearance structure	plug model	16A European standard plug
	product type	Plug and play charging
	Shell material	Gun Head - Control Box PC9330
	Equipment size	Gun head 230 * 98 * 70mm/control box 220 * 98 * 48mm [H * W * D]
	Installation method	Floor/wall mounted
	Install components	Wall mounted screw accessories
	Wiring method	Up in and down out
	Equipment weight	About 2KG
	Cable specifications	3*2.5mm ² +0.75mm ²
Electrical indicators	Cable length	5 meters [supports customized line length]
	input voltage	AC230V
	Input frequency	50Hz/60Hz
	maximum power	3.5KW
	output voltage	AC230V
	Output current	16A
Environmental indicators	standby power	3W
	usage scenarios	Indoor/Outdoor
	Working humidity	5% -95% non condensing
	working temperature	-30 +50
	Working altitude	<2000 meters
	Protection level	Gun head IP67/control box IP67
	Cooling method	Natural cooling
	Safety regulations and standards	SAEJ1772
	Flame retardant grade	UL94 V0
	Product Certification	TUV,CE,CB
Functional design	man-machine interface	LED indicator light
	communication interface	/
Packaging specifications	Box gauge/weight	505*505*298mm

safety design	Undervoltage protection, overvoltage protection, overload protection, overcurrent protection, over temperature protection, leakage protection, grounding protection, lightning protection, electrostatic protection, flame retardant protectionretardant protection
---------------	---

Application
 Suitable for charging new energy vehicles anytime and anywhere for emergency electricity use in households, outdoor travel, emergency relief, outdoor work, and other occasions.
 Minimalist Standard
 Status indicator light
 overload protection
 Leakage protection
 Grounding protection
 Over temperature protection
 Overvoltage/undervoltage protection
 Overcurrent protection



Simple Standard Type

Status Indicator Light

-  Overload Protection
-  Leakage Protection
-  Ground Protection
-  Over Temperature Protection
-  Over/Under Voltage Protection
-  Over Current Protection

