



HD-OB102 Portable Household Charger with 8A-32A Current Adjustment 3W **Numeric Display**

Basic Information

TIANJIN TOEC HUADIAN TECHNOLOGY Brand Name:

CO., LTD

HD-OB102 Model Number:



Product Specification

. Cooling Method: Natural Cooling

Protection Level: Gun Head IP67/control Box IP67

Working Temperature:

• Working Humidity: 5% -95% Non Condensing

3W · Standby Power: Maximum Power: 7KW

Timing Charge Home EV Charging Station, . Highlight:

Home EV Charging Station Gun,

EV Charger Gun 8A

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Portable Home EV Charger Gun HD-OB102, 8A-32A, 3W Low Power, LED Indicator, Timing Charge Product Description

- 1. Portable household portable charger
- 2. After charging and use, it can be carried with the vehicle
- 3. When the device is in standby mode, the power is as low as 3W, saving energy and low consumption
- 4. Three color charging indicator light, indicating charging related values
- 5. Numerical screen display, displaying real-time charging data of the charging gun
- 6.8A-10A-13A-16A-32A current gear adjustment, can be set to 0h-8h reservation charging function

Describe

The HD-OB102 charging gun is a portable charging product that meets the European Union's AC power consumption standards, with a rated AC output of maximum power of 7KW and a weight of approximately 3.4KG. It is suitable for household new energy on-board chargers, outdoor travel, emergency relief, outdoor work, and other occasions.

General specifications

General specifications		
Detailed parameters		Parameter Details
Name and model		HD-OB102
Appearance structure	plug model	32A industrial plug
	product type	Plug and play charging/scheduled
		charging/current regulation
	Shell material	Gun Head - Control Box PC9330
	Equipment size	Gun head 240 * 98 * 70mm/control box 220 * 80 * 70mm [H * W * D]
	Installation method	Floor/wall mounted
	Install components	Wall mounted screw accessories
	Wiring method	Up in and down out
	Equipment weight	About 3.4KG
	Cable specifications	3.6mm² +0.75mm²
	Cable length	5 meters [supports customized line length]
	input voltage	AC230V
	Input frequency	50Hz/60Hz
	maximum	7KW
	power	
Electrical	output voltage	AC230V
indicators	Output current	8A-10A-13A-16A-32A
	standby power	3W
	usage scenarios	Indoor/Outdoor
	Working humidity	5% -95% non condensing
	working temperature	-30 +50
	Working altitude	<2000 meters
		Gun head IP67/control box IP67
Environmental	Cooling method	Natural cooling
indicators	Safety regulations and standards	
	Flame retardant grade	UL94 V0
	Product Certification	TUV,CE,CB
Functional design	man-machine interface	LCD 1.3 inch display screen
	communication interface	
Packaging specifications	Box gauge/weight	505*505*298mm

safety design	Undervoltage protection, overvoltage protection, overload protection, overcurrent protection, over temperature protection, leakage protection, grounding protection, lightning protection, electrostatic protection, flame retardant protectionretardant
	protection

Application

Suitable for American standard new energy vehicle home emergency electricity, outdoor travel, emergency relief, outdoor work and other occasions, charging anytime and anywhere.

Customized common questions

Regarding price:

The customized products produced by our company are all for customer bulk prices for reference only. Please provide product specifications, quantities, materials, processes, and colors for quotation. We will provide accurate quotations according to your needs

Customized design:

We can provide brand design services, including logo, color, and your product packaging instructions or company profile. Regarding delivery time:

According to the order quantity and process, specific communication shall prevail.



No. 6, Mount Taishan Road, Hexi District, Tianjin