

AC230V Portable Electric Car Charger 16A European Standard Plug

Basic Information

Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY

CO., LTD

Model Number: HD-OB106



Product Specification

• Equipment Weight: About 2KG

• Cable Specifications: 3*2.5mm² +0.75mm²

• Cable Length: 5 Meters [supports Customized Line Length]

Input Voltage: AC230V
 Input Frequency: 50Hz/60Hz
 Maximum Power: 3.5KW

• Highlight: AC230V Portable Electric Car Charger,

Portable Electric Car Charger 16A

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

Portable Outdoor Power Station, 3.5KW,16A European Plug, Low 3W Standby Power Consumption

Product Description

- 1. Portable household portable charger
- 2. After charging and use, it can be carried with the vehicle
- 3. When the device is in standby mode, the power is as low as 3W, saving energy and low consumption
- 4. Three color charging indicator light, indicating charging related values
- 5. Numerical screen display, displaying real-time charging data of the charging gun

Describe

The HD-OB106 charging gun is a portable charging product that complies with the European Union's AC power consumption standards, with a rated maximum AC output power of 3.5KW and a weight of approximately 2KG. It is suitable for household new energy on-board chargers, outdoor travel, emergency relief, outdoor work, and other occasions.

General specifications

ers	Parameter Details
	HD-OB106
plug model	16A European standard plug
product type	Plug and Charge
Shell material	Gun Head - Control Box PC9330
Installation method Install Appearance components structure Wiring method	Gun head 230 * 98 * 70mm/control box 220 * 98 * 62mm [H * W * D]
	Floor/wall mounted
	Wall mounted screw accessories
	Up in and down out
weight	About 2KG
specifications Cable length	3*2.5mm² +0.75mm²
	5 meters [supports customized line length]
	AC230V
Input frequency maximum power	50Hz/60Hz
	3.5KW
output voltage	AC230V
Output current	16A
standby power	3W
usage	Indoor/Outdoor
Working humidity working temperature Working altitude	5% -95% non condensing
	-30 +50
	<2000 meters
	Gun head IP67/control box IP67
Cooling method	Natural cooling
standards Flame retardant grade Product Certification	
	UL94 V0
	TUV,CE,CB
	LCD 1.3 inch display screen/LED indicator
	light
communication interface	/
Box gauge/weight	505*505*298mm
	product type Shell material Equipment size Installation method Install components Wiring method Equipment weight Cable specifications Cable length input voltage Input frequency maximum power output voltage Output current standby power usage scenarios Working humidity working temperature Working altitude Protection level Cooling method Safety regulations and standards Flame retardant grade Product Certification man-machine interface communication interface Box

Undervoltage protection, overvoltage protection, overload safety design protection, overcurrent protection, over temperature protection, leakage protection, grounding protection, lightning protection, electrostatic protection, flame retardant protectionretardant protection

Application

Suitable for American standard new energy vehicle home emergency electricity, outdoor travel, emergency relief, outdoor work and other occasions, charging anytime and anywhere.

Plastic engineering plastic shell, copper plated silver pin contact, rubber seal

One click lid opening design, simple and convenient operation.

Compliant with multiple national standards such as CE/FCC for multiple protection and safe charging Supports wide voltage range.





TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



e outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin