

## Numerical Screen Home EV Charging Station W/NEMA 14-50P Plug Waterproof Ev Charger

Our Product Introduction

for more products please visit us on [outdoorpower-station.com](http://outdoorpower-station.com)

### Basic Information

- Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD
- Model Number: HD-AMB108



### Product Specification

- Input Voltage: AC240V
- Input Frequency: 50Hz/60Hz
- Maximum Power: 7.4KW
- Output Voltage: AC240V
- Output Current: 32A
- Standby Power: 3W
- Highlight: Home EV Charging Station W NEMA, Numerical Screen Home EV Charging Station, 50P Waterproof Ev Charger

## Product Description

**We usually export large quantities to foreign countries. Hope to find more trade partners.**

### HD-AMB108 Portable Outdoor Power Station w/NEMA 14-50P Plug

#### Product Description

1. Portable household portable charger
2. After charging and use, it can be carried with the vehicle
3. The power of the device is as low as 3W in the on-machine state, saving energy and low consumption
4. Three color charging indicator light, indicating charging related values
5. Numerical screen display, displaying real-time charging data of the charging gun

#### Describe

The HD-AMB108 charging gun is a portable charging product that meets the American AC power standards, with a rated maximum AC output power of 7.4KW and a weight of approximately 3.4KG. It is suitable for household new energy on-board chargers, outdoor travel, emergency relief, and outdoor work.

#### General specifications

Detailed parameters		Parameter Details
Name and model		HD-AMB108
Appearance structure	plug model	NEMA 14-50P
	product type	Plug and Charge
	Shell material	Gun Head - Control Box PC9330
	Equipment size	Gun head 230 * 98 * 58mm/control box 220 * 98 * 62mm [H * W * D]
	Installation method	Floor/wall mounted
	Install components	Wall mounted screw accessories
	Wiring method	Up in and down out
	Equipment weight	About 3.4KG
	Cable specifications	3*6mm <sup>2</sup> +0.75mm <sup>2</sup>
	Cable length	5 meters [supports customized line length]
Electrical indicators	input voltage	AC240V
	Input frequency	50Hz/60Hz
	maximum power	7.4KW
	output voltage	AC240V
	Output current	32A
	standby power	3W
Environmental indicators	usage scenarios	Indoor/Outdoor
	Working humidity	5% -95% non condensing
	working temperature	-30 +50
	Working altitude	<2000 meters
	Protection level	Gun head IP67/control box IP67
	Cooling method	Natural cooling
	Safety regulations and standards	SAEJ1772
	Flame retardant grade	UL94 V0
	Product Certification	UL,FCC
Functional design	man-machine interface	LED indicator light
	communication interface	/
Packaging specifications	Box gauge/weight	505*505*298mm
safety design	Undervoltage protection, overvoltage protection, overload protection, overcurrent protection, over temperature protection, leakage protection, grounding protection, lightning protection, electrostatic protection, flame retardant protectionretardant protection	

#### Application

Suitable for American standard new energy vehicle home emergency electricity, outdoor travel, emergency relief, outdoor work and other occasions, charging anytime and anywhere.


The charging current is

10A 16A 20A 24A 32A

time delay

Charging delay time

Can be set for 1-12 hours



#### Current

The charging current is

10A 16A 20A 24A 32A



#### Time Delay

The charging delay time

can be set 1~12 hour



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin