



# Automotive Lithium Battery Power Station 10000mAh Car Portable Power **Station**

# **Basic Information**

TIANJIN TOEC HUADIAN TECHNOLOGY Brand Name:

CO., LTD

HD12 Model Number:



# **Product Specification**

. Battery Capacity: 37WH/10000mAh

• Power Features: TYPE-C Charging Input /PD Output:

5V3A,/9V3A/12V3A/15V3A/20V5A 5V3A/9V3A/12V3A/15V3A,/20V5A USB1: QC3.0/5V3A/9V2A/12V1.5A USB2:5V/2A DC

Output: 12V-16.8V8A

Peak Current: 1000A/1200A

. LED Lights: Constant, Strobe, SOS

 Shell Flame Retardant V0

Grade:

-30 -65 • Operating Temperature: Product Net Weight: About 600g

 Product Packaging: Toolbox

• Highlight: Automotive Lithium Battery Power Station,

Lithium Battery Power Station 10000mAh, 10000mAh Car Portable Power Station

## **Product Description**

We usually export large quantities to foreign countries. Hope to find more trade partners.

High magnification polymer lithium-ion automotive emergency starting power supply

HD12 is a portable, outdoor emergency, and long-lasting automotive emergency power supply that meets American AC power standards. It uses a high magnification polymer lithium-ion battery and is suitable for home emergency power, outdoor travel, emergency relief, and outdoor work.

The battery capacity of this product is 10000mAh, using an IC intelligent protection chip that intelligently matches the voltage and current of the car. The nine fold protection is effective (polymer lithium battery, constant current protection, voltage stabilization protection, overshoot protection, anti backflow protection, temperature protection, short circuit protection, overcurrent protection, and over discharge protection) to ensure battery stability. It is suitable for 12V diesel gasoline vehicles, regardless of vehicle type, fearless displacement, bidirectional fast charging, high-power output, and durable.

## General specifications

General specifications	
Built-in battery	High rate polymer lithium battery
Battery capacity	37WH/10000mAh
Product Features	Display &PD&QC3.0&DC output
Power Features	TYPE-C charging input /PD output: 5V3A,/9V3A/12V3A/15V3A/20V5A 5V3A/9V3A/12V3A/15V3A,/20V5A USB1: QC3.0/5V3A/9V2A/12V1.5A USB2:5V/2A DC output: 12V-16.8V8A
Starting current	500A/600A
Peak current	1000A/1200A
LED Lights	Constant, Strobe, SOS
lifecycle	>1000 times
Fully charged time	3-4H
Shell material	PC
Shell Flame retardant grade	V0
Operating temperature	-30 -65
Product dimension	192*88*44mm(LWH)
Product net weight	about 600g
Product color matching	Can be freely matched by customers (quantity required)
Product packaging	toolbox
Tool box dimension	20.5*22.5*5.5cm (LWH)
Accessories(Default)	Intelligent jump cables

## note

- 1,Please do not use this power supply for usage scenarios outside of its design scope.
- 2, Children should avoid contact or use emergency power sources in cars to prevent accidental injury.
- 3,Do not use emergency powe humid environments to prevent leakage accidents.
- 4,Do not disassemble or repair the emergency power supply of the car without authorization. If repair is needed, please contact a professional..
- 5,Do not directly touch the leaking battery. Leaking electrolyte can cause skin discomfort. In case the electrolyte enters the eyes, rinse with clean water as soon as possible.

## Application

Suitable for household emergency electricity use, outdoor travel, emergency relief, outdoor work, and other occasionsThe emergency starting power supply is usually designed to be lightweight and compact, making it convenient for car owners to carry and operate

frequently asked question

- 1, Is the price still negotiable?
- 2, What is logistics? Express delivery?
- 3,What to do if payment fails?
- 4, Is there a minimum order quantity limit?
- 5, Is the product quality guaranteed.
- 6, How to view the order status?



( ) 13752486626 huangwei@toec-iot.com outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin