



Outdoor Portable Emergency Power Station 29600mwh 37000hwh **Battery**

Basic Information

TIANJIN TOEC HUADIAN TECHNOLOGY Brand Name:

CO., LTD

HD21 Model Number:



Product Specification

. Battery Capacity: 16000mAH/20000mAh

• Power Features: TYPE-C Charging Input /PD Output:

5V3A,/9V3A/12V3A/15V3A/20V5A 5V3A/9V3A/12V3A/15V3A,/20V5A USB1: QC3.0/5V3A/9V2A/12V1.5A USB2:5V/2A DC

Output: 12V-16.8V8A

• Peak Current: 1000A/1200A

. LED Lights: Constant, Strobe, SOS

 Shell Flame Retardant V0

Grade:

-30 -65 • Operating Temperature: Product Net Weight: About 600g

 Product Packaging: Toolbox

• Highlight: Portable Emergency Power Station 29600mwh, Portable Emergency Power Station 37000hwh,

outdoor power station 37000hwh

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

High magnification polymer lithium-ion automotive emergency starting power supply

HD21 is a portable, outdoor emergency, and long-lasting automotive emergency power supply that meets American AC power standards. It uses a high magnification polymer lithium-ion battery and is suitable for home emergency power, outdoor travel, emergency relief, and outdoor work.

The battery capacity of this product is 29600mwh/37000hwh, using an IC intelligent protection chip that intelligently matches the voltage and current of the car. The twelve fold protection is effective (polymer lithium battery, constant current protection, voltage stabilization protection, overshoot protection, anti backflow protection, temperature protection, short circuit protection, overcurrent protection, and over discharge protection) to ensure battery stability. It is suitable for 12V diesel gasoline vehicles, regardless of vehicle type, fearless displacement, bidirectional fast charging, high-power output, and durable. Car refrigerators, car vacuum cleaners, and other car appliances can all be used.

General specifications

| acriciai specifications | |
|-----------------------------|--------------------------------------------------------------|
| General specifications | |
| Built-in battery | Automotive emergency backup power integrated machine starter |
| Battery capacity | 29600mwh/37000hwh |
| Product Features | Display &PD&QC3.0&DC output |
| Power Features | TYPE-C input: 5V/2A/9V2A USB output: 5V/2A/9V2A/12V-1.5A |
| Starting current | 500A/600A |
| Peak current | 1000A/1200A |
| LED Lights | Constant, Strobe, SOS |
| lifecycle | >1000 times |
| Fully charged time | 3-4H |
| Shell material | PC |
| Shell Flame retardant grade | V0 |
| Operating temperature | -30 -65 |
| Product dimension | 192*88*44mm(LWH) |
| Product net weight | about 600g |
| Product color matching | Can be freely matched by customers (quantity required) |
| Product packaging | toolbox |
| Tool box dimension | 20.5*22.5*5.5cm (LWH) |
| Accessories(Default) | Intelligent jump cables |
| | |

note

Please do not use this power supply for usage scenarios outside of its design scope.

Children should avoid contact.

Do not use emergency powe humid environments to prevent leakage accidents.

Do not disassemble or repair the emergency power supply of the car without authorization. If repair is needed, please contact a professional..

Do not directly touch the leaking battery. Leaking electrolyte can cause skin discomfort. In case the electrolyte enters the eyes, rinse with clean water as soon as possible.

When using the emergency start power supply of a car, please pay attention to the number of uses. Generally, if the voltage of the lithium polymer battery is insufficient during emergency start ignition, it is difficult to start successfully and will consume electricity.

Application

Suitable for household emergency electricity use, outdoor travel, emergency relief, outdoor work, and other occasionsThe emergency starting power supply is usually designed to be lightweight and compact, making it convenient for car owners to carry and operate.



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



Outdoorpower-station.com