



Portable Emergency Power Station With TYPE C Charging Input And PD Output

Basic Information

Brand Name: TIANJIN TOEC HUADIAN TECHNOLOGY

CO., LTD

• Model Number: HD37



Product Specification

Battery Capacity: 16000mAH/20000mAh

• Power Features: TYPE-C Charging Input /PD Output:

5V3A,/9V3A/12V3A/15V3A/20V5A 5V3A/9V3A/12V3A/15V3A,/20V5A USB1: QC3.0/5V3A/9V2A/12V1.5A USB2:5V/2A DC

Output: 12V-16.8V8A

• Peak Current: 1000A/1200A

• LED Lights: Constant, Strobe, SOS

Shell Flame Retardant
 V0

Grade:

Operating Temperature: -30 -65
 Product Net Weight: About 600g
 Product Packaging: Toolbox

• Highlight: TYPE C Portable Emergency Power Station,

TYPE-C Charging Emergency Power Station, PD Output Emergency Power Station

Product Description

We usually export large quantities to foreign countries. Hope to find more trade partners.

High magnification polymer lithium-ion automotive emergency starting power supply

HD37 is a portable, outdoor emergency, and long-lasting automotive emergency power supply that meets American AC power standards. It uses a high magnification polymer lithium-ion battery and is suitable for home emergency power, outdoor travel, emergency relief, and outdoor work.

The battery capacity of this product is 20000mAh, using an IC intelligent protection chip that intelligently matches the voltage and current of the car. The nine fold protection is effective (polymer lithium battery, constant current protection, voltage stabilization protection, overshoot protection, anti backflow protection, temperature protection, short circuit protection, overcurrent protection, and over discharge protection) to ensure battery stability. It is suitable for 12V diesel gasoline vehicles, regardless of vehicle type, fearless displacement, bidirectional fast charging, high-power output, and durable. Car refrigerators, car vacuum cleaners, and other car appliances can all be used.

General specifications

e polymer lithium battery Ah-74WH &PD&QC3.0&DC output charging input /PD output:
Ah-74WH &PD&QC3.0&DC output charging input /PD output:
&PD&QC3.0&DC output charging input /PD output:
charging input /PD output:
/3A/12V3A/15V3A/20V5A /3A/12V3A/15V3A,/20V5A IC3.0/5V3A/9V2A/12V1.5A //2A ut: 12V-16.8V8A
0A
200A
t, Strobe, SOS
nes
14mm(LWH)
0g
reely matched by customers required)
5*5.5cm (LWH)
it jump cables

Do not use emergency power sources for usage scenarios beyond their design range to prevent danger.

Avoid children and pets from coming into contact with the power supply and connecting wires during use to prevent the risk of

Do not use emergency power supply in rainy or humid environments to prevent leakage accidents.

Do not overcharge or discharge to prevent damage to the battery due to overcharging.

Please follow the product manual for battery replacement and use batteries produced by standardized manufacturers. If the battery leaks, please replace it in a timely manner. Do not touch the skin or eyes. If accidentally touching the eyes, rinse with water as soon as possible and promptly seek medical treatment.

Suitable for household emergency electricity use, outdoor travel, emergency relief, outdoor work, The battery of the diesel gasoline vehicle is out of charge, and other occasions.



TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626



huangwei@toec-iot.com



Outdoorpower-station.com