



# **Convenient Fast 32A Wall Charger Ev Charging**

## **Basic Information**

TIANJIN TOEC HUADIAN TECHNOLOGY Brand Name:

CO., LTD

HD-1006 Model Number:



# **Product Specification**

• Plug Model: Separate Wiring Without Plug

Product Type: Swipe Card Activation

Gun Head - Control Box PC9330 . Shell Material:

Gun Head 230 \* 98 \* 70mm/control Box 280 • Equipment Size:

\* 220 \* 93mm [H \* W \* D]

• Installation Method: Pillar/wall Mounted

Install Components: Wall Mounted Screw Accessories [can Be

Installed With Columns]

• Wiring Method: Up In And Down Out

About 3.7KG • Equipment Weight:

• Highlight: Fast Wall Charger Ev Charging Gun,

32A Wall Charger Ev Charging Gun, Convenient Wall Charger Ev Charging Gun

## **Product Description**

We usually export large quantities to foreign countries. Hope to find more trade partners.

Product Name: 32A Tri color LED Indicator Light Household New Energy Vehicle Charging Station

**Product Description** 

Quick Details

- 1. Household wall mounted AC charging station, which can be installed with columns
- 2. Three color charging indicator light, indicating charging related values
- 3. Optional gold and silver glass panels, supporting customized panels

## Describe

The HD-1006 charging gun is a portable charging product that complies with the European Union's AC power consumption standards, with a rated maximum AC output power of 7KW and a weight of approximately 3.7KG. It is suitable for wall mounted household new energy charging stations and is convenient and fast.

#### General specifications

| lug model                            | Parameter Details<br>HD-1006   |
|--------------------------------------|--|
| olug model                           |  |
| -                                    |  |
| and the second                       | Separate wiring without plug   |
|                                      | Swipe card activation  |
|                                      | Gun Head - Control Box PC9330  |
|                                      | Gun head 230 * 98 * 70mm/control box 280 *<br>220 * 93mm [H * W * D]   |
| nethod                               | Pillar/wall mounted  |
|                                      | Wall mounted screw accessories [can be   |
|                                      | installed with columns]  |
|                                      | Up in and down out   |
| veight                               | About 3.7KG  |
| pecifications                        | 3*6mm² +0.75mm²  |
|                                      | 5 meters [supports customized line length]   |
| nput voltage                         | AC230V   |
| nput frequency                       | 50Hz/60Hz  |
| naximum<br>oower                     | 7KW  |
| utput voltage                        | AC230V   |
|                                      | 32A  |
|                                      | 3W   |
| sage                                 | Indoor/Outdoor   |
| iumiaity                             | 5% -95% non condensing   |
| vorking<br>emperature                | -30 +50  |
| Vorking<br>Iltitude                  | <2000 meters   |
|                                      | Gun head IP67/control box IP67   |
| Cooling method                       | Natural cooling  |
| Safety<br>egulations and<br>tandards |  |
| lauc                                 | UL94 V0  |
| ertilication                         | TUV,CE,CB  |
| neriace                              | LED indicator light  |
| ommunication<br>nterface             | /  |
| Box<br>auge/weight                   | 505*505*298mm  |
|                                      | nstallation nethod nstall omponents Viring method quipment veight cable pecifications cable length nput voltage nput frequency naximum ower utput voltage output current tandby power sage cenarios Vorking umidity vorking emperature Vorking lititude Protection level cooling method afety egulations and tandards lame retardant rade Product certification nan-machine nterface ommunication nterface lox |

|               | Undervoltage protection, overvoltage protection, overload        |
|---------------|--|
| safety design | protection, overcurrent protection, over temperature protection, |
|               | leakage protection, grounding protection, lightning protection,  |
|               | electrostatic protection, flame retardant protectionretardant    |
|               | protection   |

Matters needing attention

- 1. Do not put the product into water!
- 2. Do not heat the product or approach a fire source! Do not disassemble or modify the product without authorization! Do not forcefully strike the product! otherwise It may cause other hazards such as overheating, short circuit, fire, functional failure, and shortened lifespan of the battery.
- 3. Disassembly and assembly prohibited
- 4. It is prohibited to use non dedicated vehicles for charging, as it may cause danger;
- 5.If there is leakage, do not directly touch the leakage. The leaked electrolyte can cause skin discomfort. In case the electrolyte enters the eyes, rinse with clean water as soon as possible, do not rub the eyes, and promptly seek medical attention:

### Application

Suitable for charging anytime and anywhere in situations such as emergency electricity for American standard new energy vehicles, outdoor travel, emergency relief, and outdoor work.

Frequently Asked Questions

- 1.Can I place a sample order for a charging gun?
- 2. What is the delivery time?
- 3.Is there a minimum order quantity limit for charging gun orders?
- 4. How to transport the goods and how long will it take for delivery?
- 5. How to process charging gun orders? (Requirements, quotations, samples, deposits, production)
- 6. Is it possible to label?
- 7. How long is the warranty period?
- 8. How to handle faults?



## TIANJIN TOEC HUADIAN TECHNOLOGY CO., LTD



13752486626





Outdoorpower-station.com

No. 6, Mount Taishan Road, Hexi District, Tianjin